



Regulator



Symbols



Self relieving regulator with gauge



Non relieving regulator

- Integral 3/8 or 1/2 ports (BSPP, BSPT & NPT)
- Robust but lightweight aluminium construction
- Secondary pressure ranges 2, 4, 8 & 16 bar
- Rolling diaphragm
- Balanced valve design
- Padlockable tamperproof kit
- Pressure limiter kit
- Relieving & Non-relieving types

Options:

P3	K	R	A				N		P
BSPP (G)	1	3/8	3	Relieving	B	0 - 2 bar	No Gauge	Y	
BSPT	2	1/2	4	Non-relieving	N	0 - 4 bar	No Gauge	L	
NPT	9					0 - 8 bar	No Gauge	N	
						0 - 16 bar	No Gauge	H	
						0 - 2 bar	Gauge	Z	
						0 - 4 bar	Gauge	M	
						0 - 8 bar	Gauge	G	
						0 - 16 bar	Gauge	J	

Port size	Description	Order Code	Flow dm ³ /s *	Max bar	Min temp °C	Max temp °C	Height mm	Width mm	Depth mm	Weight g
3/8	8 bar relieving	P3KRA13BNNP	63	17	-20	80	144	60	60	465
3/8	8 bar relieving + pressure gauge	P3KRA13BNGP	63	17	-20	80	144	60	97	540
1/2	8 bar relieving	P3KRA14BNNP	73	17	-20	80	144	60	60	455
1/2	8 bar relieving + pressure gauge	P3KRA14BNGP	73	17	-20	80	144	60	97	455

*flow with 10 bar inlet pressure, 6,3 bar set pressure and 1 bar pressure drop.

For Gauges: See page 54