



ASPIREX PU/ANC

Hose Construction

PU transparent and antistatic hose having a grey, rigid PVC spiral, resistant to crush, abrasion and ozone, with antistatic 9 wires copper cord.

Food and beverage – The polyurethane used is in conformity to:

- F.D.A. – CFR 21 parts 175, 105, 177, 1680, 177,2600;
- CEE 82/711, 85/572, 89/109, 90/128, 92/30, 93/8, 95/3, 98/11

Applications

Suitable for suction of warm air, abrasion dust, warm fumes, saw-dust, wood-shavings, cement, cereal grains, sugar, and other granules.

Temperature Range

-25 °C (-13 °F) to +85 °C (+185 °F)



Suction

≤ I.D. 32 mm:	0,50 bar (365 mm Hg)
I.D. 35 mm - I.D. 102 mm:	0,40 bar (300 mm Hg)
> I.D. 102 mm:	0,30 bar (220 mm Hg)

Tolerances

On inside /outside diameter

and on weight: ± 4%

Length tolerance: ± 1%

All other technical data are subject to a ± 5% tolerance.

Burst Pressure

Suitable only for suction

IHXXXXXXXX/XX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar		
IH35576020/20	20	25	–	–	–	0,10	25
IH35576025/20	25	30,4	–	–	–	0,15	30
IH35576030/20	30	36	–	–	–	0,19	36
IH35576032/20	32	38	–	–	–	0,20	38
IH35576035/20	35	41,4	–	–	–	0,22	41
IH35576038/20	38	44,6	–	–	–	0,23	45
IH35576040/20	40	46,6	–	–	–	0,25	47
IH35576045/20	45	51,8	–	–	–	0,28	52
IH35576050/20	50	57	–	–	–	0,31	57
IH35576051/20	51	58	–	–	–	0,32	58
IH35576055/20	55	62,2	–	–	–	0,35	62
IH35576060/20	60	67,4	–	–	–	0,39	67
IH35576063/20	63	70,6	–	–	–	0,43	71
IH35576070/20	70	78,4	–	–	–	0,50	78
IH35576075/20	75	83,8	–	–	–	0,55	84
IH35576076/20	76	84,8	–	–	–	0,56	85
IH35576080/20	80	89	–	–	–	0,61	89
IH35576090/20	90	99,4	–	–	–	0,72	99
IH35576100/20	100	110,4	–	–	–	0,82	110
IH35576102/20	102	112,4	–	–	–	0,84	112
IH35576110/20	110	120,4	–	–	–	0,89	120
IH35576120/20	120	131	–	–	–	0,95	131
IH35576127/20	127	138,6	–	–	–	1,02	139
IH35576130/20	130	142	–	–	–	1,10	142
IH35576140/20	140	152,4	–	–	–	1,23	152
IH35576150/20	150	162,8	–	–	–	1,37	163
IH35576152/20	152	164,8	–	–	–	1,38	165
IH35576160/10	160	173	–	–	–	1,55	173
IH35576180/10	180	193,4	–	–	–	1,95	193
IH35576200/10	200	213,6	–	–	–	2,10	214
IH35576203/10	203	217	–	–	–	2,15	217
IH35576250/10	250	–	–	–	–	3,00	265
IH35576300/10	300	–	–	–	–	3,60	315

ASPIREX PU/ANC I.D. mm Parker ITR