




Mortar Hose Couplings and Plugs

- Swivelling Version three parts, lead in teflon slide, extremely robust and tight
- Avoids hose twist of the rigid mortar hoses for much easier application



Seals of Perbunan
55° Shore A



Handle with safety-ring and
slotted pin of steel


Suitable spare parts
(packing Unit: 10 pcs.)

Øa	Øi	h	Type No.	Type No.
36	24.5	6	MDR 25	MNH-628
43.5	28.5	6	MDR-X25	MNH-630
53.5	36.5	6	MDR 35	MNH-628
53.5	36.5	6	MDR 35	MNH-628
55	41	6.5	MDR 42	MNH-628
67	51	6	MDR 50	MNH-636

Øa	Øi	h	Type No.	Type No.
43.5	28.5	6	MDR-X25	MNH-630
53.5	36.5	6	MDR 35	MNH-628
67	51	6	MDR 50	MNH-636

Crimping Ferrules of turned steel for hydraulic crimping (inner profile exactly suitable to hose stem profile)

For Hose	Type-Size	h	Øi	Ød	Øa	Weight/pc. g	Type No.
19 x 6 mm	19/25	40	31.5	24.5	38	102	PH-19
25 x 7 mm	X25	50	41	33	50	218	PH-X25
25 x 7 mm	swivelling X25	50	41	31.3	50	220	PH-X25 DR
35 x 7 mm	35	55	49	42.5	58	275	PH-35
35 x 7 mm	swivelling 35	55	49	41	58	280	PH-35 DR
38 x 7 mm	35	55	53	45.5	61	259	PH-38
42 x 7 mm	42	55	56	50.5	65	313	PH-42
50 x 9 mm	50	60	68.5	59.5	75	302	PH-50
50 x 9 mm	swivelling 50	60	68.5	57	75	310	PH-50 DR



Screwing Stems for hydraulic crimping

For Hose	Male Thread	Suitable Ferrule	b	h	Weight/pc. g	Type No.
19 x 6 mm	G 1"	PH-19	24	69.5	125	MSTP-X25/19 T
25 x 7 mm	G 1"	PH-X25	32.5	73.5	120	MSTP-X25 T
35 x 7 mm	G 1 1/4"	PH-35	42	80	218	MSTP-35 T
38 x 7 mm	G 1 1/4"	PH-38	45	80	223	MSTP-38/35 T
35 x 7 mm	G 2"	PH-35	42	86	526	MSTP-50/35 T
42 x 7 mm	G 1 1/2"	PH-42	50	80	246	MSTP-42 T
42 x 7 mm	G 2"	PH-42	50	87	452	MSTP-50/42 T
50 x 9 mm	G 2"	PH-50	59	91	497	MSTP-50 T

