



CARBURITE 10

Hose Construction

- Tube:** Black, smooth, NBR rubber compound, resistant to oil and fuel with an aromatic content not exceeding 50 %
- Reinforcement:** Synthetic textile fabrics and embedded steel wire helix
- Cover:** Black, smooth, antistatic ($R < 1 \text{ M}\Omega/\text{m}$) NBR/SBR rubber compound, oil, fuel, abrasion, ageing and weather resistant



Applications

Designed for suction and delivery of mineral oils and fuels (with aromatic content not exceeding 50 %) in road and rail tankers, service stations and refineries. For heavy duty applications CARBURITE H 10 is recommended.

Temperature Range

-30°C (-22 °F) to +80 °C (+176 °F)
up to +100 °C (+212 °F) for oil

Suction

Max. 0,8 bar (600 mm Hg)

Tolerances

RMA steel mandrel

On inside diameter:

≤ I.D. 38 mm: ± 0,79 mm

> I.D. 38 mm: ± 1,59 mm

Length tolerance:

± 1 %

Note

On request available with built-in copper wires: /E in the textile fabrics.

On request also the HT version for high temperature.

IHXXXXXXXXXX Part Number/ Standard Length m										
	I.D.	O.D.	Working Pressure			Burst Pressure			Weight	min. Bend Radius
	mm	mm	MPa	psi	bar	MPa	psi	bar	kg/m	mm
CARBURITE 10										
IH36530099/40	19	29	1,0	150,0	10	3,0	450,0	30	0,61	120
IH36531011/40	22	32	1,0	150,0	10	3,0	450,0	30	0,67	130
IH36531004/40	25	35	1,0	150,0	10	3,0	450,0	30	0,80	150
IH36530201/40	30	40	1,0	150,0	10	3,0	450,0	30	0,92	180
IH36531012/40	32	42	1,0	150,0	10	3,0	450,0	30	0,98	190
IH36530202/40	35	45	1,0	150,0	10	3,0	450,0	30	1,05	210
IH36531002/40	38	48	1,0	150,0	10	3,0	450,0	30	1,13	240
IH36530203/40	40	50	1,0	150,0	10	3,0	450,0	30	1,18	240
IH36530212/40	42	52	1,0	150,0	10	3,0	450,0	30	1,22	252
IH36530204/40	45	55	1,0	150,0	10	3,0	450,0	30	1,31	270
IH36530205/40	50	60	1,0	150,0	10	3,0	450,0	30	1,46	300
IH36531020/40	51	61	1,0	150,0	10	3,0	450,0	30	1,49	300
IH36530206/40	60	71	1,0	150,0	10	3,0	450,0	30	1,89	360
IH36531001/40	63,5	75	1,0	150,0	10	3,0	450,0	30	2,09	380
IH36530207/20	70	82	1,0	150,0	10	3,0	450,0	30	2,47	420
IH36530208/20	75	87	1,0	150,0	10	3,0	450,0	30	2,68	450
IH36530208/40	75	87	1,0	150,0	10	3,0	450,0	30	2,68	450
IH36530213/20	76	88	1,0	150,0	10	3,0	450,0	30	2,72	460
IH36530213/40	76	88	1,0	150,0	10	3,0	450,0	30	2,72	460
IH36530209/20	80	92	1,0	150,0	10	3,0	450,0	30	2,84	480
IH36531003/20	90	104	1,0	150,0	10	3,0	450,0	30	3,64	540
IH36530211/20	100	114	1,0	150,0	10	3,0	450,0	30	4,02	600
IH36530211/40	100	114	1,0	150,0	10	3,0	450,0	30	4,02	600
IH36531019/20	110	124	1,0	150,0	10	3,0	450,0	30	4,29	660
IH36531009/20	120	134	1,0	150,0	10	3,0	450,0	30	4,65	720
IH36531050/10	150	170	1,0	150,0	10	3,0	450,0	30	7,27	900
CARBURITE H10										
IH36531100/40	38	51	1,0	150,0	10	3,0	450,0	30	1,40	240
IH36531005/40	50	64	1,0	150,0	10	3,0	450,0	30	1,93	300
IH36531024/20	100	116	1,0	150,0	10	3,0	450,0	30	4,41	600

RUBBER OIL HOSE CARBURITE 10 bar MADE IN ITALY Parker ITR